

Press Release



**JRL Advertising
& Sales Promotion, Inc.**

80 Orchard Rd.
North East,
Maryland 21901

Phone: 410-287-1336
Fax: 410-287-1334
E-Mail: JRLadv@comcast.net

For Immediate Release

Custom Stainless Steel Check Valves

Jaeco stainless steel Poppet and Ball check valves can be customized to meet the requirements of specific applications. Normally available in 1/4, 3/8", 1/2", 3/4" and 1" IPS sizes with pressure breaks of 2 or 10 PSI, custom valves are available in a wide range of additional sizes and with different break pressures.

Poppet valves come standard with Viton™ or Teflon™ O-rings. Ball valves come with a 316 SS ball standard. Other o-ring and ball materials are available.

Both valves have at rated pressures to 2500 PSI. Poppet valves have a temperature range of -15°F to + 400°F; ball valves have a -20°F to +650°F range. Jaeco check valves are widely used on any liquid system that require a spring loaded check valve for positive, no drip, shutoff and/or backflow protection.

Jaeco also manufacturers a wide range of Diaphragm and Packed Plunger metering pumps, and SS compression fittings.

XXX

For more information contact: Rich Murdy, Jaeco Fluid Systems, Inc., 17 Lee Blvd., Suite, D, Malvern, PA 19355-1234. Toll Free: 877-778-3456, Fax: 610-407-7211, e-mail: rmurdy@jaecofs.com, web: www.jaecofs.com